

常用型号规格

	型号规格	外径F值	导管有效长度(cm)	最大适配导丝 (in)	侧孔数量	末端弯形
冠脉	K03-500400100	5F	100	0.038	0	AL I
	K03-600400100	6F	100	0.038	0	AL I
	K03-500500100	5F	100	0.038	0	AL II
	K03-600500100	6F	100	0.038	0	AL II
	K03-500700100	5F	100	0.038	0	AR I MOD
	K03-500800100	5F	100	0.035	0	ARII MOD
	K03-604000100	6F	100	0.038	0	JL3.5
	K03-504000100	5F	100	0.038	0	JL3.5
	K03-504100100	5F	100	0.038	0	JL4
	K03-604100100	6F	100	0.038	0	JL4
	K03-504400100	5F	100	0.038	0	JL4.5
	K03-505000100	5F	100	0.038	0	JR3.5
	K03-605100100	6F	100	0.038	0	JR4
	K03-505100100	5F	100	0.038	0	JR4
	K03-605200125	6F	125	0.038	0	JR 4 MOD
	K03-606200100	6F	100	0.038	0	MP A2
	K03-506606110	5F	110	0.038	6	PIG
	K03-606606110	6F	110	0.038	6	PIG
	K03-506700110	5F	110	0.038	0	PIG 145°
	K03-508502065	5F	65	0.038	2	RDC A2
外周	K03-401700065	4F	65	0.035	0	C2
	K03-501700100	5F	100	0.038	0	C2
	K03-401700100	4F	100	0.035	0	C2
	K03-501800065	5F	65	0.038	0	C3
	K03-401800065	4F	65	0.035	0	C3
	K03-502400100	5F	100	0.038	0	H1
	K03-402400100	4F	100	0.035	0	H1
	K03-506000100	5F	100	0.038	0	MP A1
	K03-406000100	4F	100	0.035	0	MP A1
	K03-406100125	4F	125	0.035	0	MPAI(I)
	K03-506100125	5F	125	0.038	0	MPAI(I)
	K03-406605100	4F	100	0.035	5	PIG
	K03-506605100	5F	100	0.038	5	PIG
	K03-508700080	5F	80	0.038	0	RH
	K03-408700080	4F	80	0.038	0	RH
	K03-409100100	4F	100	0.035	0	SIM1
	K03-509100100	5F	100	0.038	0	SIM1
	K03-509200100	5F	100	0.038	0	SIM2
	K03-409200100	4F	100	0.035</		

产品介绍

满足顾客需求,持续创新改进

柔软的导管尖端

降低对血管的损伤

适宜的编织加强结构

增加导管扭控性能和支撑性能

耐高压

最大耐压1200PSI

良好的形状保持功能

使其顺利到达预期位置

良好的显影性

增加医生手术时的可视性